



Office de la propriété
intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An Agency of
Industry Canada

PCT/CA

03/019574

07 JANUARY 2004 07.01.04

PCT/CA 03/1957


*Bureau canadien
des brevets
Certification*

*Canadian Patent
Office
Certification*

La présente atteste que les documents
ci-joints, dont la liste figure ci-dessous,
sont des copies authentiques des docu-
ments déposés au Bureau des brevets.

This is to certify that the documents
attached hereto and identified below are
true copies of the documents on file in
the Patent Office.

Specification and Drawings, as originally filed, with Application for Patent Serial No:
2,416,083, on January 10, 2003, by MANFRED A. A. LUPKE AND STEFAN A.
LUPKE, for "Flow Distributor for Die Tooling of Pipe Mold Equipment with Remote
Extruder".



**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Sylvie Lévesque
Agent certificateur/Certifying Officer
January 7, 2004
Date

Canada

(CIPO 68)
04-09-02

OPIC  CIPO

- 13 -

ABSTRACT OF THE DISCLOSURE

Equipment used in the molding of plastic pipe includes die tooling provided with a plastic flow distributor at the upper end of the die tooling. The plastic flow distributor is adjustable to provide an even distribution of plastic from an extruder into at least one die passage within the die tooling.

- 1 -

FLOW DISTRIBUTOR FOR DIE TOOLING OF PIPE MOLD EQUIPMENT
WITH REMOTE EXTRUDER

FIELD OF THE INVENTION

5

The present invention relates to equipment including an extruder and die tooling used in the molding of plastic pipe.

10 BACKGROUND OF THE INVENTION

A traditional plastic pipe molding apparatus includes an extruder which feeds molten plastic directly to one or more interior passages of die tooling which
15 leads to a molding region of the extruder. The one or more die passages can be used to make single or even ribbed pipe.

The above apparatus suffers from the drawback that
20 the extruder and the die tooling are fixed in position relative to one another. This necessitates relative large die tool which is expensive and which takes a substantial amount of time to heat. Space saving and heating benefits can be achieved by locating the extruder
25 at a location remote from the die tooling and then using a plastic feed from the extruder to the die tooling. However, according to known practice, these benefits are more than offset by the fact that with the current design i.e., the design of the extruder being fixed relative to
30 the die tooling the extruder is able to feed directly into the die passage of the tooling. Accordingly, distribution of the plastic from the extruder around the mouth of the die passage is achieved in a relatively simple manner. The same is not true when working with a
35 remotely located extruder which will not necessarily align directly with the mouth of the die passage.

- 2 -

Accordingly, using existing technology it is very difficult to take advantage of the benefits provided when separating an extruder from die tooling equipment of a pipe molding apparatus because such separation makes it very difficult to produce an even distribution of molten plastic from the extruder into the die passage. Without such even distribution the resulting pipe is produced with inconsistencies in the wall or walls of the pipe.

10 SUMMARY OF THE PRESENT INVENTION

The present invention relates to equipment used in the molding of plastic pipe which takes advantage of the benefits achieved by separating an extruder from die tooling without suffering from the drawbacks of such a separation.

More particularly, the present invention relates to equipment used in the molding of a plastic pipe in which the equipment comprises a plastic supply providing molten plastic for making the pipe and die tooling which is located remotely of the plastic supply.

The die tooling has an internal die passage to carry the molten plastic to a molding region where the pipe is shaped. It further has an upstream end fitted with a flow distributor. The die passage has a ring shaped mouth covered by the flow distributor at the upstream end of the die tooling.

The equipment further includes a plastic feed from the plastic supply to the flow distributor. The flow distributor is then adjustable to produce an even distribution of the molten plastic which it receives from the plastic supply around the ring shaped mouth of the die passage.

- 3 -

According to an aspect of the invention the die tooling has multiple passages and the flow distributor has multiple outlets which are adjustable for each of the die passages.

According to another aspect of the invention the equipment uses a single extruder which feeds to the multiple flow outlets of the flow distributor. According to yet another aspect of the invention the equipment uses multiple extruders each of which feeds to an individual one of the flow outlets from the flow distributor.

According to still another aspect of the invention the equipment uses multiple extruders which can for example, be used to extrude different types of plastic materials. Each of the extruders feeds to each of the flow outlets from the flow distributor. In this aspect of the invention the equipment further includes valve means to selectively open and close each of the extruders to the flow distributor so that one can choose which one of the extruders is to be used in making the pipe.

BRIEF DESCRIPTION OF THE DRAWINGS

The above as well as other advantages and features of the present invention will be described in greater detail according to the preferred embodiments of the present invention in which;

Figures 1, 2 and 3 are all schematic views of equipment used in the molding of plastic pipe according to different embodiments of the present invention;

Figure 4 is a front view of the plastic flow distributor used in any one of the embodiments of Figures

- 4 -

1, 2 and 3.

**DETAILED DESCRIPTION ACCORDING TO THE PREFERRED
EMBODIMENTS OF THE PRESENT INVENTION IN WHICH:**

5

Figure 1 shows molding equipment generally indicated at 1 used in a pipe molding operation for forming plastic pipe. Equipment 1 comprises an extruder 2 which feeds to die tooling generally indicated at 3. This die tooling receives, as to be described later in detail, molten plastic from the extruder and delivers it to a mold region (not shown) in which the plastic pipe is formed. Typically this mold region is made up of a plurality of moving mold blocks having profiled faces for shaping the pipe. Located within the mold region is a cooling plug 7 against which the interior surface of the pipe is formed.

In the embodiment shown, die tooling 3 includes first and second die passages 4 and 9 respectively. Die passage 4 has a passage outlet 5 and die passage 9 has a passage outlet 11. These two passages which extend longitudinally of the die equipment have a ring like configuration with passage 9 being located outwardly around passage 4. Each of the passages has a ring shaped mouth at the upstream end of the die tooling 3 which is covered by a plastic flow distributor generally indicated at 25. This plastic flow distributor is in the form of a plate assembly also to be described later in detail.

30

As can be seen in Figure 1 of the drawings extruder 2 is located remotely of die tooling 3. This achieves a number of benefits. Firstly, the die tooling itself is substantially shorter in length than conventional die tooling using an onboard extruder, e.g. the die tooling is probably half the length or less of

35

- 5 -

conventional die tooling. With this arrangement there are substantial savings with respect to the actual die tooling and furthermore the die tooling is much more easily and quickly heated than conventional die tooling.

5

In addition, the remote location of the extruder 2 relative to die tooling 3 does not require at a single location the large space necessitated by die tooling having an onboard extruder. In contrast, the die tooling itself can be placed in one location with relatively small space requirements and the extruder can be placed in another location.

According to the present invention a plastic feed generally indicated at 15 extends from extruder 2 to flow distributor 25. In order to do so the product feed comprises an individual conduit 17 feeding directly off of extruder 2. Conduit 17 eventually leads to branch feed lines 21 and 23 with a connecting branch between branches 21 and 23. A metering device generally indicated at 19 is provided at the mouth of branch 20 where this connecting extends from branch line 21 to branch line 23.

The plate assembly of flow distributor 25 comprises a first plate portion 27 having an outlet path as indicated at 29 which aligns with the mouth of die passage 9. Branch line 21 connects with the flow distributor so as to feed through the outlet 29 of plate portion 27 into die passage 9.

The plate construction of the flow distributor further includes plate portion 31 having an outlet path as indicated at 33 which aligns with the mouth of die passage 4 at the upstream end of the die tooling. Branch line 23 connects with plate portion 31 so as to feed

- 6 -

through flow distributor outlet 33 into die passage 4.

By way of example only, Figure 4 shows the rear surface of flow distributor 25. Here it will be seen that the outlets from the two plate portions are not localized but rather are distributed around the mouths of the two die passages. This is highlighted by the solid line flow path markings of Figure 4.

Returning to Figure 1 the plastic from extruder 2 flows along conduit 17 as far as meter 19. This flow meter which is adjustable for flow distribution purposes will set the amount of molten plastic to flow along line 21 and along connecting line 20 to line 23. Line 21 feeding through flow distributor 25 is used to carry plastic to die passage 9 feeding into the mold tunnel through passage outlet 11 in forming part of the pipe wall while line 23 feeds plastic through the flow distributor into passage 4 and out outlet 5 in forming another part of the pipe wall.

Figure 2 shows a further embodiment of the invention in which the equipment uses two extruders 2a and 2b rather than the single extruder shown in Figure 1. This setup uses the same die tooling 3 and same flow distributor 25. It additionally uses the same branch or feed lines 21 and 23.

What differs between the Figure 1 and Figure 2 embodiments is that in Figure 2, individual conduits 17a and 17b extend from the two extruders 2a and 2b. Conduits 17a feeds directly to branch line 21 which in turn feeds directly to die passage 9. Conduit 17b feeds directly to branch line 23 which then feeds to die passage 4. There is no connecting passage between the branches 21 and 23. According in this embodiment one part

- 7 -

of the pipe wall is formed from the plastic of one of the extruders and another part of the pipe wall is formed from the plastic of the other extruder.

5 Another feature of the present invention which is used in both the embodiment of Figure 1 and the embodiment of Figure 2 is the provision of ball connectors 18 in each of the supply lines. These ball connectors, which regardless of the position in which
10 they are set keep the plastic feed system in a closed condition allowing different positionings of the extruders relative to the die tooling.

 Figure 3 shows another embodiment of the invention
15 once again using the same die tooling 3 fitted with a flow distributor 25 at the upstream end of the die tooling. The function and fitting of flow distributor 25 relative to the die tooling is identical to that described with respect to Figures 1 and 2 of the
20 drawings.

 In this particular embodiment the equipment includes extruders 2c and 2d. These extruders can be used to extrude different types of plastic materials to
25 the die tooling. They may also be used for extruding the same type of material. Furthermore, they can be used simultaneously with one another or they can be used independently of one another.

30 It will be seen that extruder 2c feeds from a conduit 17c out of that particular extruder. Extruder 2d feeds from a conduit 17d. A valve 41 is located in conduit 17c and a valve 43 is located in conduit 17d.

35 Branch lines 21 and 23 feed to flow distributor 25 in the same manner as shown in Figures 1 and 2 of the

- 8 -

drawings. A connecting branch 22 connects across the upstream ends of branches 21 and 23. A valve 45 is located in connecting branch 22.

5 By closing valve 45 in connecting branch 22 and by having valves 41 and 43 open the equipment of Figure 3 operates in the same manner as the equipment shown in Figure 2, i.e., conduit 41 feeds along branch 21 to the flow distributor. Conduit 43 feeds along branch 23 to
10 the flow distributor. No plastic is allowed to flow across connecting branch 22. Accordingly, the plastic from extruder 2c is used to make the part of the pipe wall emanating from die passage 9 while extruder 2d is used to make the part of the pipe wall emanating from die
15 passage 4.

In order to make the pipe entirely from the plastic of extruder 2c valves 41 and 45 are opened. Valve 43 is closed. In this configuration the plastic
20 will flow along conduit 17c past valve 41 and down branch line 21. The plastic will additionally flow along branch line 22 past valve 45 and down branch line 23. The plastic cannot flow past the closed valve 43.

25 If it is desired to make the pipe entirely from the plastic of extruder 2d valves 43 and 22 are opened and valve 41 is closed. Under these conditions the plastic from extruder 2d flows along conduit 17d past valve 43 and down branch line 21. The plastic
30 additionally flows along branch line 22 where it is diverted by the closed valve 41 into branch line 21.

It will be seen from the description above that even though much of the setup for each of the individual
35 embodiments is consistent from one embodiment to another the equipment itself is extremely adaptive to use a

- 9 -

single extruder, multiple extruders and multiple extruders extruding different types of plastic materials. In each of these embodiments the die tooling is the same as is the flow distributor used at the upstream end of the die tooling.

One of the key features to the present invention lies in the fact that the flow distributor and in particular the two plate portions 27 and 31 are adjustable at different locations around each of the plate portions for the most efficient flow of plastic to the die tooling. In Figures 3 and 4 of the drawings it will be seen that the flow distributor 25 includes numerous different adjustment members 51 and 53 which can either be tightened or loosened to adjust the gap at the outlets of the two plate portions relative to the die passage mouths. Note that the adjustments of the plate portions are done independently of one another.

For example, the flow of plastic to the flow distributor from each of the extruders will be strongest at the localized location where the plastic enters the flow distributor. However, the plastic must be evenly distributed or spread completely around the ring like mouth of each of the die passages. Therefore the adjustment means must be setup to decrease the plastic flow at or near the location where the plastic enters the flow distributor and to cause the plastic to flow more evenly to the weaker flow areas at the passage mouth farther away from the source of plastic. The provision of multiple adjustment points around the periphery of the two plate portions of the flow distributor enables the required adjustments at each of the plate portions so as to provide consistent wall thickness around the pipe produced using the equipment.

- 10 -

Although various preferred embodiments of the present invention have been described in detail, it will be appreciated by those skilled in the art that variations may be made without departing from the spirit
5 of the invention or the scope of the appended claims.

- 11 -

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:**


1. Equipment used in the molding of plastic pipe,
5 said equipment comprising a plastic supply which provides molten plastic for making the pipe, die tooling having an internal die passage to carry the molten plastic to a molding region where the pipe is shaped, the die tooling having an upstream end fitted with a flow distributor the
10 die passage having a ring shaped mouth covered by the flow distributor at the upstream end of the die tooling, the plastic supply being located remotely of the die tooling and said equipment including a plastic feed from the plastic supply to the flow distributor, the flow
15 distributor being adjustable to produce an even distribution of the molten plastic from the plastic supply around the ring shaped mouth of the die passage.
2. Equipment as claimed in Claim 1 wherein said die
20 tooling includes a second die passage having a ring shaped mouth which is outwardly around the mouth of the first die passage and which is also covered by the flow distributor, the flow distributor being further adjustable to produce an even distribution of the molten
25 plastic from the plastic supply around the mouth of the second die passage.
3. Equipment as claimed in Claim 2 wherein said flow
30 distributor comprises a plate assembly secured to the upstream end of said die tooling, said plate assembly including a first plate portion which feeds to the mouth of the first die passage and a second plate portion which feeds to the mouth of said second die passage, said first and second plate portions both being adjustable and being
35 adjustable independently of one another.


- 12 -


4. Equipment as claimed in Claim 2 wherein said plastic supply comprise a single extruder and wherein said plastic feed comprises a single conduit from said extruder to first and second supply branches of said plastic supply, said first supply branch feeding to a first outlet path of the flow distributor around the mouth of the first die passage, the second supply branch feeding to a second outlet path of the flow distributor around the mouth of the second die passage.

5. Equipment as claimed in Claim 2 wherein said plastic supply comprises first and second extruders, said plastic feed comprising a first conduit from said first extruder to a first outlet path of said flow distributor around the mouth of said first die passage and a second conduit from said second extruder to a second outlet path of said flow distributor around the mouth of said second die passage.

6. Equipment as claimed in Claim 2 wherein said plastic supply comprises first and second extruders, said plastic feed comprising a first conduit from said first extruder and a second conduit from said second extruder, a first supply branch feeding to a first outlet path of the flow distributor around the mouth of the first die passage, a second supply branch feeding to a second outlet path around the mouth of the second die passage, and a connecting branch between said first and second supply branches, both said first and said second conduits from said first and second extruders feeding to said connecting branch of said plastic feed and said plastic supply including valve means for selecting opening and closing said first and second conduits relative to said connecting branch.







53
← 25

FIG 4

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.